

Special power transformer for circlotron stereo integrated amplifiers with power rating up to 2 x 50 W.
Recommended tube types KT 88, 6550 A, EL 34, 6L6 GC and similar ones. Filter capacitors with 500 V rating are necessary. Filament voltages are designed for 12.6 V DC heating.

Power handling	320 VA	pinning
Primary	115 V 115 V	(1-2) (3-4)
Secondary 1	18 V/0.2 A	(6-7)
Secondary 2	18 V/0.2 A	(8-9)
Secondary 3	13 V/6 A	(10/11-13/14)
Secondary 4	22 V/0.05 A	(16-17)
Secondary 5	322 V/0.16 A	(19-20)
Secondary 6	322 V/0.16 A	(22-23)
Secondary 7	322 V/0.16 A	(25-26)
Secondary 8	322 V/0.16 A	(28-29)
Secondary 9	65 V/0.05 A	(31-32)
Secondary 10	65 V/0.05 A	(34-35)
Secondary 11	65 V/0.05 A	(37-38)
Secondary 12	65 V/0.05 A	(40-41)
Core type	MD 102 B	
Dimensions	length 120 mm width 102 mm height 89 mm	
Mounting	bolts M 5	
Weight	ca. 4.9 kg	
Connectors	solder lugs	